



**24VPSC-25W, 24V Battery Solar Pulse
Charger Desulfator, 25W**
Part #: 735X689
NSN: Pending

Description:

Rated at 0.833 Amps, the 25-Watt Pulse Solar Charger charges and desulfates all 12-Volt lead-acid batteries (including VRLA, AGM, gel and flooded cell) on vehicles or equipment stored outside. No AC power is needed as the sun's energy is harnessed to prevent the normal loss of battery power on stored vehicles, generators and heavy equipment no matter how long they sit unused.



This unit utilizes our unrivaled solar charging system combined with our patented high frequency pulsing circuit, Pulse Technology, to ensure batteries start when needed no matter how long vehicles or equipment sit unused outside. Pulse Technology reverses the naturally occurring process of battery sulfation - the main cause of battery failure. This allows batteries to accept, store and release maximum power all the time extending battery life.

Safe, reliable and weatherproof, this unit prevents dead batteries by keeping them in like-new condition indefinitely. A LED light indicates the circuit is energized and the unit is working.

Specifications:

Input Electrical:	Solar Powered
Output Electrical:	833 mA
Output Voltage:	33 VOC
Circuit Box Dimensions:	4.9" x 1.8" x 1"
Solar Panel Dimensions:	14.4" x 17.9" x .125"
LED	Indicates circuit is energized and unit is working
Box to Clip Wire Length:	50"
Box to Panel Wire Length:	25'
Shipping Weight:	4.2 lbs.

Contact Information:

Roy Johnson • VP of Military and Government Programs • 315-489-8823 • rjohnson1@twcny.rr.com
Tom Pigorsh • Field Support Western US Military Programs • 719-331-0329 • tom.pigorsh@comcast.net
Adam Hagenston • North US National Guard/Reserve Component/AF • 575-635-9931 • adam.hagenston@yahoo.com
Briza Justice • Government & Military Quotes and Sales • 817-329-6099 Ext. 152 • bjustice@pulsetech.net

www.pulsetech.net