

Xtreme Charge Battery Charger



Smart, Safe and Fully-Automatic Pulse Maintenance Charger

- Charges and maintains 12-Volt lead-acid VRLA, AGM and flooded batteries
- Extends battery life with desulfating pulses
- Fully-automatic microprocessor controlled technology
- Cannot overheat or overcharge the battery
- Reverse battery protection and indication
- Sparkless operation
- Includes both heavy-duty clamps and lugs
- Fuse protected cables
- Rugged plastic protective case
- Five-Year Limited Warranty



This innovative, state-of-the-art battery charger automatically knows what to do so you don't have to be a battery expert to use it. Unlike other smart chargers on the market, you don't need to select the battery type or the proper charge rate for your car's battery to avoid the risk of unsafe or improper charging.

There's no guess work because the fuse-protected, spark-proof Xtreme Charge® works on any type of 12-Volt lead-acid battery – VRLA, AGM and flooded. Proprietary algorithms combined with microprocessor controlled technology measure the battery's voltage and current to automatically determine and deliver the precise charge rate based on the size and condition of the individual battery, both initially and continuously throughout the five-stage charge process.

Xtreme Charge is more than a battery charger and maintainer. During the maintenance cycle, PulseTech's patented, optimized frequency pulsing constantly

works to minimize and reduce naturally occurring battery sulfation – the main cause of battery failures. By reducing the size and number of lead sulfate deposits on the battery plates that negatively affect your battery's ability to accept, store and release energy, your battery will charge deeper, maintain greater reserve capacity and last longer – up to five times longer.

The quick disconnect feature allows you to permanently attach lugs to the battery and easily switch between lugs and clamps. The status light column shows you when the unit power is on, pulsing and charging. The battery light column indicates the percentage of the battery's state of charge – 25%, 50%, 75% or 100%.

Specifications

Input Electrical	
Input Voltage	110-240 V ac
Input Current	0.8 Amps maximum
Input Frequency	50-60 Hz
Min. Voltage for Startup	≥ 4 V dc
Output Electrical	
Output Current	2.5 A dc Maximum
Output Voltage, Bulk Charge	14.8 V dc
Absorption to Float Charge Threshold	Voltage: 14.2 V Under Charge and Charge Current < 0.75 A dc
Desulfating Pulse Peak Amplitude	250 mA Typical
Desulfating Pulse Frequency	22 kHz to 28 kHz
Pulse Rise Time	< 1 microsecond

Mechanical/Physical Characteristics	
Dimensions	7.90" L x 3.50" W x 2.20" H (201mm L x 88.9mm W x 55.9mm H)
Weight	1.53 lbs. (694 g)
Shipping Weight	2.41 lbs. (1.09 kg)
Enclosure	ABS Plastic Rated 94-V0
Power Cord Length	6' (1.83 m)
Battery Cable Length	6 ft. (1.83 m)
Lug/Clamp Cable Length	2 ft. (0.61 m)

Environmental	
Operating Temperature	0°F to 130°F (-18°C to 54°C)
Storage Temperature	0°F to 150°F (-18°C to 66°C)

Indicators	
Power On	No Connection
Bad Battery	Pulsing
Charging	Test
Battery State of Charge	25%, 50%, 75%, 100%
Safety and Compliance	
UL Listed	

Ordering Information

100X010 Part Number
XC-100-P Model Number

PulseTech
Products Corporation
800-580-7554 www.pulsetech.net